

# M2000TT *Intermec* ©

Blow label applicator with Intermec printer

- Intermec reliable and rugged 24/7 printers PX4 or PM4 based side and top applicator
- M2000TT offers all Intermec printer functionality with wide range of ready to use software
- M2000TT enables printing from Windows or Unix based program in network



MICROSTYR + INTERMEC =



M2000TT



## Product data

### Application

- Direct Thermal (DT) and Thermal Transfer (TT) printing of adhesive labels

### Physical Characteristics

- LxHxW: 510 x 238 x 285 mm
- Weight: 15 kg

### Print Specifications

- Max. Print Width: 110 (4,3 in)
- Max. Length with extended memory:

### Print Speed

- 100 - 300 mm/s (4 - 12 ips) variable

### Available software

- Intermec Printer Application Server™
- ERPLabel™ for SAP™ R/3®.

### Print Resolution

- 8 dots/mm (203 dpi)
- 11.8 dots/mm (300 dpi)

### Label/Ticket/Tag

- Max. Width: 120 mm (4,72 in)
- Min. Width: 50,8 mm (2.0 in)
- Thickness: 60 to 250µm (2.4 to 10 mil)
- Label Roll max diameter: 213 mm (8.38 in)
- Label Roll Core: 38-76 mm (1.5-3.0 in)

### Ribbon Roll

- Ribbon roll max diameter: 80 mm (3.15 in) or to 600 m (23 600 in) in length
- Ribbon Roll Core: 25 mm (1.0 in)
- Ribbon Type: Wax, wax/resin, resin

### Standard Interfaces:

- EasyLAN 10/100BaseT internal Ethernet
- RS-232, up to 115.2 kB/s, USB 2.0
- Wand interface for EasySet™ System

### Optional interface:

- EasyLAN Wireless internal Ethernet

ok