

M500TT *Intermec* ©

Easy and economic applicator with Intermec printer

- Intermec reliable and rugged printers based - side and top applicator

M500TT offers all Intermec printers functionality with wide range of ready to use software

M500TT enables printing from Windows or Unix based programs in network

MP500 can work stand alone without any PC



MICROSTYR + Intermec =
M500TT



Product data

Application

- Direct Thermal (DT) and Thermal Transfer (TT) printing of adhesive labels, tickets and tags.

Physical Characteristics

- LxHxW: 900 x 300 x 480 mm
- Weight: 15 kg

Print Specifications

- Max. Print Width: 104mm (4.09 in)

Print Speed

- Print speed up to 120 labels/min

Available software

- Intermec Printer Application Server™
- ERPLabel™ for SAP™ R/3®.

Print Resolution

- 8 dots/mm (203 dpi),
- 11.8 dots/mm (300 dpi)

Label/Ticket/Tag

- Max. Width: 104 mm (4.09 in)
- Thickness: 60 to 250µm (2.4 to 10 mil)
- Label Roll max diameter: 213 mm (8.38 in)
- Label Roll Core: 38-76 mm (1.5-3.0 in)

Ribbon Roll

- Ribbon roll max diameter: 83 mm (3.27 in) corresponding up to 450 m (1475 ft) in length
- Ribbon Roll Core: 25 mm (1.0 in)
- Ribbon Type: Wax, wax/resin, resin

Standard Interfaces:

- RS-232, up to 115.2 kB/s
- USB 1.1
- EasyLAN Internal Ethernet 100/10BaseT
- I2C-bus for cutter
- Wand interface for EasySet™ System

Optional interface:

- EasyLAN Wireless, internal 802.11b/g Wireless Ethernet

ok