

# M500 - SATO®

Dispenser like applicator with Sato printer top, side

- Sato CL4NX reliable and rugged printers based side and top applicator
- M500 Sato offers all Sato printer functionality with wide range of ready to use software
- M500 Sato enables printing from Windows or Unix based program in network



MICROSTYR + Sato =  
M500 Sato

## Product data

### Application

- Direct Thermal (DT) and Thermal Transfer (TT) printing of adhesive labels, tickets and tags.

### Physical Characteristics

- LxHxW: 900 x 300 x 480 mm
- Weight: 15 kg

### Print Specifications

- Max. Print Width: 104-167mm

### Print Speed

- Print speed up to 120 labels/min

### Available software

- Nice Label™ design software

### Print Resolution

- 8 dots/mm (203 dpi),
- 11.8 dots/mm (305 dpi)
- 24 dots/mm (609 dpi)

### Label/Ticket/Tag

- Max. Width: 104-167 mm
- Label Roll max diameter: 210 mm
- Label Roll Core: 38-76 mm (1.5-3.0 in)

### Ribbon Roll

- Ribbon roll max length: 600m
- Ribbon Roll Core: 25 mm (1.0 in)
- Ribbon Type: Wax, wax/resin, resin

### Standard Interfaces:

- RS-232
- USB 2.0
- Ethernet
- Bluetooth

### Optional interface:

- WLAN

### Memory:

- 2GB RAM - 2 MB Flash

ok