

CROSSLABEL 2013

CrossLabel - Multi Label Applicator

- PC Windows based stand alone system
- Mutivac, Dixi packaging machine compatible
- Database connectivity
- Product and traded unit label support
- Unlimited amount of formats and products



MICROSTYR + Intermec =
M-CrossLabel



Product data

Application

- Direct Thermal (DT) and Thermal Transfer (TT) printing of adhesive labels

Physical Characteristics

- LxHxW: 1000 x 700 x 280 mm
- Weight: 20 kg

Print Specifications

- Max. Print Width: 104 mm

Print Speed

- max 250 mm/s
- Print Resolution
- 203 dpi, 300dpi, 400dpi
- Speed Multivac: aprox 35 steps per minutue

Power

- 100-230 VAC / 50-60Hz
- Operating temperature 4-40°C (41-104°F)
- Air pressure - clean

Memory

- 16-64 Mb Flash
- 512Mb - 2Gb SDRAM

Label/Ticket/Tag

- Max. Width: 104 mm (4,09 in)
- Min. Width: 40 mm (1,5 in)
- Thickness: 58 to 180µm
- Label Roll max diameter: 200 mm (11,8 in)
- Label Roll Core: 40-76 mm

Ribbon Roll

- Ribbon roll: 450m in length
- Ribbon Roll Core: 25,4 mm (1.0 in)
- Ribbon Type: Wax, wax/resin

Standard Interfaces:

- 2 x RS-232C, up to 115.2 kB/s, USB 2.0
- 2x Ethernet LAN (10BaseT/100BaseTx)
- Wireless LAN (802.11b/g)
- 4 x USB ports
- Bluetooth



Manufactured by MICROSTYR , Box 2040, 125 02 ÄLVSJÖ, Sweden
Tel. +46 8 647 77 42

<http://www.microstyr.se> , email: order@microstyr.se